

SPECIFICATIONS

		TVX-2000M	TVX-2000W
Capacity	kN	2,000	2,000
Stroke Length	mm	25 / 30	25 / 30
Strokes Per Minute	SPM	100-450	100-500
Force Point	mm	3.2 (1.6 at 300 spm or more)	3.2 (1.6 at 300 spm or more)
Die Height	mm	440	440
Die Height Adjustment	mm	60	60
Slide Area	mm	1,700 x 650	2,000 x 800
Upright Opening	mm	460	460
Bolster Size	mm	1,700 x 950	2,000 x 1000
Bolster Thickness	mm	240	240
Bed Opening	mm	1,400 x 350	1,700 x 350
Bolster Opening	mm	1,400 x 300	1,700 x 300
Main Motor	kW	45	55
JIS Static Accuracy		Special Grade	Special Grade
Upper Die Weight	kg	Max. 1,200	Max. 1,300
Gross Weight	kg	48,000	50,000

		TVX-3000M	TVX-3000W
Capacity	kN	3,300	3,000
Stroke Length	mm	25 / 30	25 / 30
Strokes Per Minute	SPM	100-410	100-450
Force Point	mm	3.2 (1.6 at 300 spm or more)	3.2 (1.6 at 300 spm or more)
Die Height	mm	480	440
Die Height Adjustment	mm	60	60
Slide Area	mm	2,300 x 800	2,700 x 1,000
Upright Opening	mm	540	550
Bolster Size	mm	2,300 x 1,000	2,700 x 1,000
Bolster Thickness	mm	240	240
Bed Opening	mm	2,000 x 400	2,400 x 400
Bolster Opening	mm	2,000 x 380	2,400 x 350
Main Motor	kW	55	55
JIS Static Accuracy		Special Grade	Special Grade
Upper Die Weight	kg	Max. 1,500	Max. 2,000
Gross Weight	kg	75,000	65,000

SPECIFICATIONS

		TVX-3300-330	TVX-3300-370
Capacity	kN	3,300	3,300
Stroke Length	mm	30 / 40	30 / 40
Strokes Per Minute	SPM	100 - 360/300	100 - 360/250
Force Point	mm	3.2 (1.6 at 300 spm or more)	3.2 (1.6 at 300 spm or more)
Die Height	mm	520-620	520-620
Die Height Adjustment	mm	60	60
Slide Area	mm	3,300 x 900	3,700 x 1000
Upright Opening	mm	690	690
Bolster Size	mm	3,300 x 1,000	3,700 x 1,200
Bolster Thickness	mm	240	240
Bed Opening	mm	3,000 x 500	3,200 x 500
Bolster Opening	mm	3,000 x 450	3,200 x 450
Main Motor	kW	55	55
JIS Static Accuracy		Special Grade	Special Grade
Upper Die Weight	kg	Max. 3200	Max. 4000
Gross Weight	kg	130,000	140,000